Construction:

Frame : 92 x 85mm

Sash : 92 x 107mm, multi laminated wood, joined on length. Any shape and size is possible.

Material:

Spruce, Pine, Meranti, Oak, Accoya

Acoustic insulation:

Acoustic insulation 32-49dB (depending on the selected glazing or panel unit)

Thermal transittance for IV92 profile:

 U_d Standard glazing = 0,73 W/m²K

 U_d Standard panel 33% = 0,73 W/m²K

 $U_{d \text{ Large } glazing} = 0.81 \text{ W/m}^2\text{K}$

U_{d Large panel 33%} = 0,81 W/m²K

Glazing

Standard: 4 float/18 Ar w.e. / 4 float / 18 Ar w.e. /4 lowe with Ug = 0,5 W/m²K

Panel: 12 mm Spruce + 30 mm insulation + 10 mm Spruce = 52mm (11 = 0.85 W/m²/V) (0.72 = 22 + 20 + 22)

= 52mm ($U_p = 0.85 \text{ W/m}^2\text{K}$) (0,73 22 + 30 + 22)

Warm edge is offered as gift at any order.

Hardware:

Standard hardware Roto DoorSafe with 5 locking points and Simonswerk Baka hinges.

Optional fittings with extra safety class: RC1, RC2 or RC3 Colour:

Any kind of colour from RAL chart is availble, also a set of transparent colours from Remmers.

Seals:

We use 3 seals Q-lon as standard for this system. The core is made of polyurethane foam, outer coating of polyethylene is weatherproof, resistant to UV radiation and pollution. Avalible in colours: brown, white, black or grey.

Silicone:

Silicone colour matching wood colour: white, transparent or brown

Handles:

Standard handles are the one's from Hoppe in colors white, brown, silver, bronze or gold.

Type of window openings

The system D92 is suitable for all types of openings, windows, balcony doors, tilt and slide doors. Thermal conductivity values are calculated in accordance with SR EN ISO 10 077-1 / 10 077-2 and measurements are made on the following dimensions:

Standard : 1000 x 2100 mm Large (2 wings) : 1800 x 2100mm

Uf softwood $(0,11 \text{ W/m}^2\text{K}) = 0,91 \text{ W/m}^2\text{K}$

Uf soft/hardwood (0,13 W/m²K) = 1 W/m²K

Uf hardwood (0,18 W/m²K) = 1,25 W/m²K





